

MATERIAL SAFETY DATA SHEET

Print date: 29-Oct-2008

Revision Number: 1

Revision date: 29-Oct-2008

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PHONE NUMBERS

Emergency Medical (24 HOUR)	800/447-4545
Emergency Transportation/CHEMTREC (24 HOUR)	800/424-9300
Other Emergency Information (24 HOUR)	518/475-5222
Non-Emergency Information	413/448-5800

PRODUCT IDENTIFICATION

PRODUCT IDENTIFIER: NORYL
SA120 SA90 SA9000 WCA871A WCA875 WCA901 WCD835 WCD841U
WCD891B WCD933 WCP761 WCP921 WCP921A WCA063 WCV065
WCV072 FNH2160 731 731F FE1410PW GFN2 GFN2F GFN3 GFN3
SE1GFN1 SE1GFN2 SE1GFN3 SE100X SE1X PX0844 PX9406P

PRODUCT DESCRIPTION: Polyphenylene ether [CASRN 25134-01-4]/High impact polystyrene [CASRN 9003-55-8] and/or polystyrene [CASRN 9003-53-6] blend
PRODUCT USE: Synthetic thermoplastic polymer.
May be used to produce molded or extruded articles or as a component of other industrial products.

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Components listed below are physical or health hazards as defined in the Hazard Communication Standard. The quantities represent typical or average values for the materials shown. Additional compositional data are provided in Section 15, REGULATORY INFORMATION, subject to supplier notification requirements.

<u>Component Name</u>	<u>%</u>	<u>CAS Number</u>	<u>OSHA PEL</u>	<u>ACGIH TWA</u>	<u>GE Recommended Exp. Limits</u>
GLASS	10 - 30	65997-17-3	No PEL establishe d	10 mg/m3 (resp. fr.)	Not established

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- Pellets with slight or no odor.
- Spilled material may create slipping hazard.
- Can burn in a fire creating dense toxic smoke.
- Molten plastic can cause severe thermal burns.
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

HMIS Ratings: Health = 0; Flammability = 1; Reactivity = 0; PPE = B

POTENTIAL HEALTH EFFECTS

INGESTION: No hazard in normal industrial use.
 SKIN ABSORPTION: No absorption hazard in normal industrial use.
 EYE CONTACT: Can cause mechanical irritation if dusts are generated.
 SKIN CONTACT: Unlikely to cause irritation even on repeated contact.

CHRONIC / CARCINOGENICITY

NTP: Not Tested.
 OSHA: Not Regulated.
 IARC: Not Listed.

NOTE: OSHA, IARC and/or NTP have listed carbon black and heavy metals, present in some colorants, as carcinogens. If these colorants are present in this product, they are shown in SECTION 2. These colorants are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

Processing fumes may cause irritation to the eyes, skin, and respiratory tract. In cases of severe exposure, nausea and headache can also occur.

Grease-like processing fume condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury to skin.

MEDICAL RESTRICTIONS: There are no known human health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

SECTION 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention if irritation develops or persists. After initial flushing, remove any contact lenses.
 SKIN: Wash with soap and water. Get medical attention if irritation develops or persists. For hot product, immediately immerse in or flush affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.

INGESTION:	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop.
INHALATION:	No specific treatment is necessary since this material is not likely to be hazardous by inhalation.
PROCESSING FUMES:	Processing fumes inhalation may be irritating to the respiratory tract. If symptoms are experienced remove victim from the source of contamination or move victim to fresh air and obtain medical advice.

SECTION 5: FIRE FIGHTING MEASURES

FIRE FIGHTING:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.
EXTINGUISHING MEDIA:	Water spray and foam. Carbon dioxide and dry chemical are not recommended because their lack of cooling capacity may permit re-ignition.
CONDITIONS OF FLAMMABILITY:	Requires a continuous flame source to ignite.
AUTOIGNITION TEMPERATURE:	490 C (914 F), estimated
EXPLOSION DATA:	Material not sensitive to mechanical impact but is sensitive to static discharge under dust cloud conditions.
HAZARDOUS COMBUSTION PRODUCTS:	Intense heat, smoke, carbon dioxide, carbon monoxide, hydrocarbon fragments

SECTION 6: ACCIDENTAL RELEASE MEASURES

GENERAL:	Gather and store in a closed container pending a waste disposal evaluation. Allow molten material to solidify before disposal.
----------	--

SECTION 7: HANDLING AND STORAGE

HANDLING:	Follow recommendations on label and in processing guide. Prevent contact with skin and eyes. Use good industrial hygiene practices. Provide adequate ventilation. Secondary operations such as grinding, sanding, or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation: employ bonding, grounding, venting, and explosion relief provisions in accordance with accepted engineering practices.
STORAGE:	Store in a cool dry place. Avoid excessive heat and ignition sources.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate personal protection. Local ventilation requirements must be determined to limit exposure to processing fumes in the workplace.

PERSONAL PROTECTION

EYE/FACE: Wear safety glasses with side shields or chemical goggles. In addition, use full-face shield when cleaning processing fume condensates from hoods, ducts, and other surfaces.

SKIN: When handling pellets or powder, avoid prolonged or repeated contact with skin. Wear long pants, long sleeves, well insulated gloves, and a face shield during melt processing. Appropriate clothing - including chemical resistant gloves - should be worn to prevent contact with processing fumes condensate.

RESPIRATORY: When using this product at elevated temperatures, implement engineering systems, administrative controls, or a respiratory protection program (including a respirator approved for protection from organic vapors, acid gases, and particulate matter) if processing fumes are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator approved for protection from dust.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Solid

COLOR: Plastic pellet with slight odor.

MELTING POINT: This product does not exhibit a sharp melting point but softens gradually over a wide range of temperatures.

VAPOR PRESSURE (mmHg): Negligible.

SPECIFIC GRAVITY (WATER = 1): >1

WATER SOLUBILITY: Insoluble.

% VOLATILES: Negligible

EVAPORATION RATE: Negligible.

OCTANOL/WATER PARTITION COEFFICIENT: Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

REACTIVITY: Not reactive under recommended conditions of handling, storage, processing, and use.

CONDITIONS TO AVOID:

Do not exceed melt temperature recommendations in product literature. In order to avoid autoignition/hazardous decomposition of hot thick masses of plastic, purgings should be collected in small, flat, shapes or thin strands to allow for rapid cooling. Quench in water. Do not allow product to remain in barrel at elevated temperatures for extended periods of time: purge with a general purpose resin. (See Section 8 for respiratory protection advice.)

HAZARDOUS DECOMPOSITION PRODUCTS

Processing fumes evolved at recommended processing conditions may include trace levels of the following materials: alkylphenols, aldehydes and alcohols, aliphatic amines, dimethylcyclohexanone, trimethylanisole, dihydrobenzofuran, styrene, 4-vinylcyclohexene, carbon dioxide, carbon monoxide

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE HEALTH HAZARDS

ACUTE ORAL:

Oral LD50 Rat >15 g/kg Oral toxicity is estimated from tests on similar materials.

EYE CONTACT:

Product not considered primary eye irritant. When similar products, in finely divided form, were placed into the eyes of rabbits, slight transient redness or discharge occurred. This is consistent with the expected slightly abrasive nature of the resin particles.

SKIN CONTACT:

Product not considered primary skin irritant. Draize Skin Primary Irritation Score (rabbit) for similar products, in finely divided form, for a 24-hour exposure is 0. Not expected to be a skin sensitizer based on results of Modified Buehler Guinea Pig Sensitization Test from similar products. Dermal LD50 (rabbit) > 2g/kg, estimated.

SUBCHRONIC HEALTH HAZARDS

SUBCHRONIC TOXICITY:

In a 13 week dust inhalation study, laboratory rats were exposed to up to 50 mg/m³ PPO dust for 6 hrs/day for 13 weeks with a 13-week non-exposure recovery period. There was no evidence of systemic toxicity at the highest dose. Localized toxicity was observed in the lungs and regional lymph nodes of the 50 mg/m³ exposure group. These findings decreased in severity in the 7 and 1 mg/m³ exposure groups. A no adverse effect level for PPO is estimated to be 7 mg/m³ and a no observable effect level is 1 mg/m³.

CHRONIC HEALTH HAZARDS

CARCINOGENIC PROPERTIES

NTP:

Not Tested.

OSHA:

Not Regulated.

IARC:

Not Listed.

SECTION 12: ECOLOGICAL INFORMATION

GENERAL:

This material is not expected to be harmful to the ecology.

SECTION 13: DISPOSAL INFORMATION

WASTE DISPOSAL: Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

POSSIBLE EPA WASTE CODES: No data.

SECTION 14: TRANSPORTATION INFORMATION

REGULATORY STATUS: Not Regulated.

SECTION 15: REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA): This product is in compliance with all rules and orders of TSCA.

WHMIS PRODUCT CLASSIFICATION: Not a controlled product.

If any components in this product are SARA 313 listed as reportable, they are shown below. The quantities listed for elements represent typical or average values for compounds containing the element.

Component	CAS Number	%
No SARA 313-listed chemicals in this product.		

If any components in this product are known to the State of California to cause cancer and/or are reproductive hazards, they are listed below:

Component	Reason Listed	CAS Number	%
Not Applicable			
Toluene	developmental toxicity - initial date 1/1/91	108-88-3	0.01 - 0.1

SECTION 16: OTHER INFORMATION

Prepared by: Product Stewardship

® AVP, COLORXPRESS, CYCOLAC, CYCOLOY, CYTRA, ENDURAN, GELON, GELOY, GEMAX, GTX, LEXAN, LEXGUARD, LOMOD, MAGIX, NORYL, NORYL GTX, NORYL PPX, POLYMERLAND, PPO, PPX, PREVEX, SOLLX, SUPEC, ULTEM, VALOX, VISUALFX, XENOY and XYLEX are registered or pending trademarks of the General Electric Co.

DISCLAIMER: This Material Safety Data Sheet [MSDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person,

including for compliance with other laws. SABIC does not warrant the suitability for use of this MSDS for any other material or product not specifically identified herein. SABIC does not warrant the accuracy or authenticity of this MSDS unless it has been obtained directly from SABIC, or posted or viewed on a SABIC website. Modification of this MSDS, unless specifically authorized by SABIC, is strictly prohibited. This MSDS is based on information, that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under General Electric Company's control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. GENERAL ELECTRIC COMPANY MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

ABBREVIATIONS:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CAS: Chemical Abstracts Service
- CFR: Code of Federal Regulations
- CPR: Cardiopulmonary Resuscitation
- EPA: Environmental Protection Agency
- HMIS: Hazardous Material Identification System (National Paint and Coatings Association)
- IARC: International Agency for Research on Cancer
- OSHA: Occupational Health and Safety Administration (U.S.)
- NTP: National Toxicology Program
- PEL: Permissible Exposure Limit
- PPE: Personal Protective Equipment
- SARA 313: Superfund Amendments and Reauthorization Act, Section 313
- TLV: Threshold Limit Value
- TSCA: Toxic Substance Control Act
- WHMIS: Workplace Hazardous Materials Information System (Canada)